

Powder Binder Spreader

alpha 15 B
17 B



**With conveyor belt
Chassis mounted**

To be mounted on existing truck- or dumper chassis equipped with power take-off, operating at engine speed, with a 400 Nm torque

Modern concept, offering following features

- Binder transfer by means of a conveyor belt, width 1 m
- Product delivery rate in proportion to the drive speed
- Adjustable product delivery rate from 3 to 60 kg/m², depending on the drive speed
- Spreading by means of stainless steel cellular rotor, diameter 520 mm
- Rotor of 4 separate sections, each with independent drive and operation
- Access to spreading compartment
- Computer management in Can-Bus configuration, mounted inside anti-choc box with monochrome 3,8" display
- Fast and watertight high-quality electric connexions
- Moulded plugs
- Predisposition for filter cartridges for venting during filling procedure
- Very limited dust dispersion
- Hydraulic pumps driven by tractor PTO
- Manhole

Capacity
α 15 B: **15 m³**
α 17 B: **17 m³**

Spreading width
2.400 mm

Width
α 15 B: **2.750 mm**
α 17 B: **2.750 mm**

Height
α 15 B: **1.900 mm**
α 17 B: **1.900 mm**

Length
α 15 B: **5.750 mm**
α 17 B: **6.350 mm**

OPTIONS

Complete filtering device including air compressor

Air compressor

Radar speed detection

Sprinkling system with water tank and pump

Integrated weighing system

Printer